

THE ALL-NEW SOLID 510 PLAYER CARD PRINTER



It's here..



Exclusive
XPRESS
CONNECT




Open Card Printing

This feature allows for the Casino Staff to quickly replace a printer minimizing downtime. The Exclusive "XPress Connect Technology Key" is a swappable USB key that stores the IP Address and card format required for the AS/400 or Windows to print a card.

The SOLID-510 OC Card Printer with OpenCard Format is an Ideal Solution for Casinos and other Gaming Venues to create Player and VIP Cards, Room Keys and Employee Badges



Monochrome Ribbons



SOLID Series FEATURES

- ✓ Ultra-Fast Printing w/ Mag Encoding (6-7 Sec.)
- ✓ Exclusive XPress Connect Hot Swap Technology
- ✓ Ribbon Saving Technology
- ✓ Easy Front Loading of Cards and Ribbons
- ✓ Exception Card Slot for VIP Cards
- ✓ Quiet Operation
- ✓ Solid Metal Frame

XPRESS
Systems

THE ALL-NEW SOLID 510 PLAYER CARD PRINTER

**2 Year
WARRANTY**
Service Depot

- New Input Hopper with Exception Card Slot
200 cards with cover open | 100 cards in default



- Removable -
Output Hopper for Kiosks



**XPress
CONNECT**



- Hot-Swap Technology
- High Speed Printing
- Enhanced FINE™ Imaging Technology
- State-of-the-art CPU
- Reduced Printing Noise
- All-in-one Lock system (*Option)
- Easy to Handle Laminate Film Cartridge

- Rear-side Stacker for Increased Speed
(up to 100 cards, *Option)



- Front-side Mag Encoding (*Option)
- Support of Transparent Card
- Support CR79 Type (Factory-installed, *Option)

*Print Speed : May change under specific condition.

Specifications and availability may change without notice.

SPECIFICATIONS

PRINTING

- Print Type Dye-Sublimation
- Print Area Edge to Edge
- Resolution 300dpi
- Dual Sided Printing Option (with Flipper)

CARD

- Card Feeding Automatic
- Card Size ISO CR80 or ISO CR79 (Option-Factory installed)
- Card Thickness 0.38mm (15mil), 1.0mm (40mil)
- Card Type PVC, PET, Composite PVC

PRINT SPEED

- Monochrome 5 sec./card (720 cards/hour)
- YMCKO Front-in & Front-out : Max. 17 sec./card (212 cards/hour)
Front-in & Back-out : Max. 16 sec./card (225 cards/hour)

CAPACITY

- Input Hopper 100 cards / 200 cards with cover open
- Output Hopper Front : 40 cards / Back : 100 cards (Optional Back-side Stacker)

SYSTEM

- Memory 64MB RAM
- Display & Button 2 Line LCD / 2 LED Buttons
- Supported Platforms Microsoft Windows 7/ 8/ 10, Mac OS, Linux
- Communication USB, Ethernet (Option)
- Power Free Voltage (AC100/ 240V, 50~60Hz) / 48W
- Temperature/Humidity 15~35℃ / 35~70%
- Security Physical Lock & Kensington Lock (Option)

DIMENSIONS / WEIGHT


- Millimeter (WxLxH) 165 x 390 x 210
- Inch (WxLxH) 6.5 x 15.4 x 8.3
- Kg/lbs 4.5 / 10

ENCODING OPTIONS

- Magnetic ISO7811 (Track I, II, III Read/ Write, HiCo/ LoCo), JIS II
- Contact ISO 7816 (ID-1)
- Contactless MIFARE, ISO 14443 (Type A/ B), ISO 15693, DESFIRE, iCLASS

CERTIFICATIONS

**Authorized
Dealer:**



Distributed by: **IdentiSys**

7630 Commerce Way
Eden Prairie, MN 55344
888.437.9783 Toll Free
www.identisys.com