



DATA MATRIX



COMPACT, PORTABLE METAL TAG EMBOSSESSER WITH 2D DATA MATRIX OPTION

The **ME550 FLEXI TAG DATA MATRIX** is a portable metal tag embossing solution designed to mark alphanumeric characters and **2D DATA MATRIX** barcodes on different aluminum and steel tags sizes. The **2D DATA MATRIX** barcode has the great advantage of containing a high volume of data on limited space. With a completely renewed design and new features, the **ME550 FLEXI TAG DATA MATRIX** is an advanced solution that can be integrated into any existing factory or office network.

7" color touchscreen display with high resolution

The **ME550 FLEXI TAG DATA MATRIX** is equipped with a built-in 7" WGA LCD touchscreen display with simple and easy to use icon and buttons. The user can access and manage machine functions through a multi-level menu in an easy and intuitive way. The configuration of the machine can be protected by password for high security and data protection.

IoT (Internet of Things) remote access and management

- **Web services:** The machine set-up and operations can be entirely managed remotely via the web or through the use of VNC (Virtual Networking Computing) client, using a personal computer or other devices connected to the Customer's network.
- **Data transfer:** Data import/export and the machine updating can be managed from any device connected to the embosser via Ethernet by using the FTP protocol (file transfer protocol).

USB (type A, type B), Ethernet and WiFi

The **ME550 FLEXI TAG DATA MATRIX** can be connected to a personal computer, to load data and start production, or to another device, such as keyboard, barcode reader or other if needed.

The **ME550 FLEXI TAG DATA MATRIX** is a completely self-contained tag marking machine that is easy to transport, and designed to operate in harsh industrial environments. It is ideal for component and production line identification and traceability applications.



USED BY

- AUTOMOTIVE PLANTS
- SHIPYARDS
- STEEL PLANTS
- MILITARY
- LOGISTICS MANAGEMENT
- INDUSTRIAL MANUFACTURERS



IDEAL FOR

- BODY & VIN PLATES
- MILITARY ID TAGS
- INVENTORY
- ASSET CONTROL
- ID & TRACKING TAGS
- CABLE / HOSE TAGS
- TAGS FOR GALVANIZED OR HEAT-TREATED PROCESSES
- COMPONENT ID
- SERIAL NUMBER TAGS

FEATURES AND SPECIFICATIONS

MODEL NAME

ME550 FLEXI TAG DATA MATRIX

PLATE AND FEEDER

Dimensions

Rectangular tag: 52 x 29 ÷ 65 x 60 mm - 2.05 x 1.14 ÷ 2.56 x 2.36 in (WxH)



min. 52 x 29 mm - 2.05 x 1.14 in



max. 65 x 60 mm - 2.56 x 2.36 in

Materials

Aluminum, stainless steel

Thickness

0,3556 ÷ 0,70 mm - 0.014 ÷ 0.0275 in

Input hopper

Up to 250 plates capacity (0,4 mm / 0.0157 in) - automatic feed only

Output hopper

External collection tray

MARKING

Technology

Embossing or debossing

Wheel capacity

60 slots

Type set

Simplex 2, Block USA, Block 5, OCRB1

Embossing area

See picture. Up to 10 lines / 20 characters

Performance

105 tags per hour based on 55 characters (144 tags per hour based on 45 characters)

COMMUNICATION AND SOFTWARE

Interface

USB 2.0 port (device and host), Ethernet. WiFi (optional)

Software

PowerTag PC application proprietary software compatible with

Windows 8.1/10/11, MacOS (Intel64, da 10.x onwards), Linux

PowerTag USB on USB key for multiple use

Protocol

Multiembosser

Optional: Cim, Xon-Xoff, Stored Format default, Stored Format Selected and Pound-Pound

HARDWARE

System

CPU Arm Cortex-A8 / RAM 256 MB, with flash-disk and file system Linux O.S. based

Power supply

Universal switching power supply 100-240 Volts; 50 or 60 Hz

Power consumption

300 Watt max

Operating environment

Temperature: 5°÷ 40°C 7 / 41°÷104° F, relative humidity 30% ÷ 90°

VARIOUS

Others

Built in touch screen 7", multi-language user interface management: English, Spanish, Italian
Innovative embedded software up-grade system thru pen drive and web server
Machine configuration protected by password for high security and data protection
Easy to carry handle, no packaging required


CERTIFICATIONS



WARRANTY




EMBOSSING AREA



Dashed area not usable height
3,5 mm - 0.137 in



DIMENSION



WEIGHT

26 Kg / 57.3 lbs



SOFTWARE

power tag
LITE

optional
power tag
EVO



Distributed by:



7630 Commerce Way
Eden Prairie, MN 55344
888.437.9783 Toll Free
www.identisys.com