



125 KHZ PROXIMITY CARDS



IdentiSys proximity credentials deliver the same performance as the industry's largest name brand products. IdentiSys cards are ISO compliant, compatible with most 125kHz systems and cost less than name brand equivalents.

Choose from clamshell prox cards or printable standard PVC and PVC-PET composite prox cards, with or without magnetic stripe. IdentiSys cards are available in a large variety of bit formats, including the common industry standard 26 Bit H10301 format and commonly used 37 Bit H10302 or H10304 format.

Credential Form Factor	Clamshell	ISO PVC Cards	ISO Composite Cards	ISO PVC Cards w/ Magnetic Stripe	ISO Composite Cards w/ Magnetic Stripe
Dimensions	3.385 x 2.125 x 0.075 in (86 x 54 x 1.9 mm)	3.37 x 2.125 x 0.033 in (85.6 x 54 x 0.84 mm)			
Weight	0.317 oz / 8.9 g	0.212 oz / 6 g			
Read Range**	Up to 5 in / 127 mm				
Slot Punch	Vertical	Vertical or Horizontal			
Operating Temperature	-49° to 158°F / -45° to 70°C				
Material	Hard Shell: ABS Cover Label: PVC	PVC	PVC-PET	PVC	PVC-PET
IdentiSys Part Number	IPC-9000	IPC-9010	IPC-9020	IPC-9030	IPC-9040
Comparable Part Numbers	1326, 7410, 4000	1386, 7510, 4010	1586, 7510, 4020	1336, 7510M1, 4030	1536, 7510M1, 4032
Product					

© IdentiSys Inc. | All rights reserved.

IdentiSys part numbers and formats are similar in functionality and performance to part numbers and formats referenced. All other trademarks belong to their respective companies.

Technical data is subject to change without notice.
2024-11



7630 Commerce Way
Eden Prairie, MN 55344
888.437.9783 Toll Free
www.identisys.com

IdentiSys Format	Format Code	Issuer	Bits	Possible Facility Codes		Possible Card Serial Numbers	Notes
26AD	AWID	AWID	26	0 – 255		0 – 65,535	
26A 26D	H10301	General Distribution	26	0 – 255		0 – 65,535	
26DMP	D12200	Digital Monitoring Products (DMP)	26	0 - 127		0 - 131,071	FC is 7 bits long, card number 17 bits
26I 26ID	40134	Indala (E/O Parity)	26	0 – 255		0 – 65,535	
26IF	41106	Indala (E/E Parity)	26	0 – 255		0 – 65,535	
26IG		Indala (O/O Parity)	26	0 – 255		0 – 65,535	
27B	P3BSB27	BSB Electronics	27	0 - 8191		0 - 16,383	
32D			32	0 - 16,383		0 - 65,535	
32E	I11201	Intercon Security Limited	32	0-8,191		0-32,767	
32H 32Q	Quadrakey	Honeywell	32	n/a		0 – 4,294,967,295	
32D	D10202	DSX	33	Default 17		0 – 16,777,215	Default FC 17
34A	A14001		34	0 – 255 0		0 – 1,048,575	
34B	i909482A		34	– 127		0 – 131,071	
34C 34S	C10001	Requires Issue Code (0-7)*	34	0 – 7*	0 – 8,191	0 – 65,535	
34D	H10306		34	0 – 65,535		0 – 65,535	
34E 34N	N10002	Honeywell (Northern)	34	0 – 65,535		0 – 65,535	
34F 34G	I10001	Geoffrey/Schlage	34	0 – 4,095		0 – 1,048,575	
34J	JCI	Requires Issue Code	34	0 – 7*	0 – 65,535	0 – 65,535	
35D	H5XXXX	Corp1000	35	0 – 4,095		0 – 1,048,575	
35E	H5XXXX		35	0 – 8,191		0 – 1,048,575	
36B	C15001	Keyscan	36	0 – 255		0 – 65,535	
36C	C10202	Continental (A17601)	36	0 – 65,535		0 – 65,535	
36D	S12906	Simplex	36	Default 17		0 – 16,777,215	Default FC 217
36E	L11601	Lenel	36	0 – 1,023		0 – 262,143	
36I	i10601		36	0 – 8,191		0 – 131,071	
36J	N901157A	Napco	36	0 – 255		0 – 67,108,863	
36M	H10313M	HID 36 9 Digit ID Code + Facility Code (36 bits)	36	0-15		0-1,073,741,823	
36S	S10601		36	0 – 16,383		0 – 1,048,575	
37A	A10202		37	0 – 4,095		0 – 524,287	
37C	S10701		37	0 – 1,023		0 – 65,535	
37D 37H	H10302	HID 37 No FC	37	n/a		0-34,359,738,367 (limited to 4,294,967,295 for IdentiSys cards)	
37E 37X	H10304	HID 37 with FC	37	0 – 65,535		0 – 524,287	
37G	S10401	AMAG	37	Default 9		0 – 536,870,911	Default FC 9
37I	I10304		37	0-63		0 – 65,535	
40C	C10106	GE – CasiRusco	40	Up to 12 digit number, must begin with “15”			
				151,552 – 155,632	0 – 457,681		
				Example: 155632 457681			
40D	H10314		40	0 – 4,095		0 – 65,535	
48A	Corp”2000”	New Corp1000 format	48	0 – 4,194,303		0 – 8,388,607	
64K	Kantech XSF	Requires Extended Family Code & Family Code	64	Ext. Fam: Must Provide		0 – 65,535	

Other formats are available on demand or can be developed.

If you have any questions or a format you have is not listed, please inquire with Sales@IdentiSys.com